



04/05/00

4-6-00

THE COMMISSIONER OF PATENTS AND TRADEMARKS
Washington D.C. 20231
Box Patent Applications

Case Docket No. FUSA 17.211
Filed by Express Mail
(Receipt No. EL522391655US)
on April 5, 2000
pursuant to 37 CFR 1.10
by Lydia Gonzalez

S I R:

Transmitted herewith for filing is: ☒ a new application
☐ a c-i-p application of S.N. _____ filed _____

Inventor(s): Osamu SEKIHATA

For: FRAME FORWARDING INSTALLATION

Enclosed are:

- ☒ 17 sheets of drawings.(Figs. 1A,1B,2-18)
☒ Specification, including claims ad abstract (43 pages)
☒ Declaration
☒ An assignment of the Invention to FUJITSU LIMITED
☒ A certified copy of Japanese Application No(s). 11-171941
☒ An associate power of attorney
☐ A verified statement to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27
☒ Post card
☒ Recording fee (as indicated below)
☒ Information Disclosure Statement, PTO-1449, copies of 2 references
☐ Other _____
☐ Other _____

	Col. 1	Col. 2
FOR:	NO. FILED	NO. EXTRA
BASIC FEE		
TOTAL CLAIMS	18-20 =	0
INDEP CLAIMS	7-3 =	4
<input type="checkbox"/> MULTIPLE DEPENDENT CLAIMS PRESENTED		

*If the difference in Col. 1 is less than
zero, enter "0" in Col. 2

SMALL ENTITY	
RATE	FEE
	\$345
x 9 =	\$
x 39 =	\$
x 130 =	\$
TOTAL	\$

OTHER THAN A SMALL ENTITY	
RATE	FEE
	\$690
x 18 =	\$
x 78 =	\$312
x 260 =	\$
TOTAL	\$1002

☐ Please charge our Deposit Account No. 08-1634 the amount of _____ to cover the filing fee and recording fee (if any)

☒ A check in the amount of \$1042.00 to cover the filing fee and the recording fee (if any) is enclosed.

☒ The Commissioner is hereby authorized to charge payment of any fee associated with this communication or credit overpayment to Deposit Account No. 08-1634. A duplicate copy of this sheet is enclosed.

Helfgott & Karas, P.C.
60th Floor
Empire State Building
New York, New York 10118-6098
(212)643-5000

Date: April 5, 2000

Any fee due with this paper, not fully
covered by an enclosed check, may be
charged on Deposit Acct No. 08-1634

Respectfully Submitted,

- ☒ Aaron B. Karas, Reg. No. 18,923
☐ Samson Helfgott, Reg. No. 23,072
☐ Leonard Cooper, Reg. No. 27,625
☐ Linda S. Chan, Reg. No. 42,400
☐ Jacqueline M. Steady, Reg. No. 44,354
☐ Harris A. Wolin, Reg. No. 39,432



Filed by Express Mail
(Receipt No. ELS22396SS4S)
on 4/5/00
pursuant to 37 C.F.R. 1.10.
by 262462.

SPECIFICATION

TITLE OF THE INVENTION

FRAME FORWARDING INSTALLATION

BACKGROUND OF THE INVENTION

5 This invention relates to technology for
maintaining communication quality and communication
reliability in a local-area network (LAN). This
technology is applicable to frame forwarding
installations such as routers and switches that
10 construct a LAN, is highly likely to be applied in the
future and is essential in terms of improving the
quality and reliability of networks.

More specifically, the present invention relates to
a frame forwarding installation in a network such as a
15 LAN and, more particularly, to a frame forwarding
installation for sending frames, which require a real-
time property and quality/reliability, to plurality of
paths, and to a frame forwarding installation for
accepting, and transmitting to a destination terminal,
20 only a first arriving frame of identical frames that
arrive from a plurality of paths, and discarding frames
other than the first arriving frame.

It is required that the quality and reliability of
communication in networks be improved. In order to
25 improve the quality of communication in a conventional
LAN, frame transmission delay and transmission
fluctuation (a variance in transmission delay) are
reduced. To achieve this, processing speed is raised by

using hardware to implement routing processing or by executing preferential processing in regard to frames having priority.

Achieving an improvement in reliability is carried
5 out by adopting so-called redundancy or by adopting a so-called hot-standby method, in which the LAN device itself is provided with redundancy to establish active and standby channels so that the standby channel will be switched to automatically if the active channel fails.

10 Meanwhile, it has been decided that there will be one path from a transmission source to a destination in a LAN. In order to generate the path automatically, the optimum path is calculated using a routing protocol referred to as RIP (Routing Information Protocol) or
15 OSPF (Open Shortest Path First). If a failure occurs, the path can be changed dynamically. There are also occasions where static routing is performed to decide a static path using an address table. In either case, however, there is only one end-to-end path in a LAN at
20 one time.

Thus, in the prior art, an improvement in reliability and quality is attempted on a single path. As a consequence, even if it is attempted to improve quality by improving processing performance at each node
25 in a network or by performing preferential control, frame processing is delayed if a point along the path develops a very high load, thus making it difficult to maintain communication quality. Further, even if it is

attempted to improve reliability by adopting redundancy in devices and modules, this does not redress faults in the transmission line, for example, and it is therefore not possible to assure perfect reliability.

5

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to arrange it so that communication quality can be maintained even if a path becomes congested and so that communication can be continue even if a path fault
10 develops.

Another object of the present invention is to provide a frame forwarding installation for sending frames, which require a real-time property and quality/reliability, to a plurality of paths leading to
15 a destination, thereby maintaining the quality and reliability of communication.

Still another object of the present invention is to provide a frame forwarding installation for accepting, and transmitting to a destination terminal, only a first
20 arriving frame of identical frames that arrive via a plurality of paths, and discarding frames other than the first arriving frame, thereby maintaining the quality and reliability of communication.

A further object of the present invention is to
25 provide a network in which communication quality can be maintained even if a path becomes congested and in which communication can be continue even if a path fault develops.

According to a first aspect of the present invention, a frame forwarding installation on the side of a transmitting terminal sends a received frame in the direction of a destination over a plurality of paths if
5 a host application of the transmitting terminal is a real-time application. A frame forwarding installation on the side of a destination terminal sends a first arriving frame to the destination terminal and discards later arriving frames.

10 In this case, the frame forwarding installation on the side of the transmitting terminal determines whether the application of a host layer is a real-time application upon referring to a header of the received frame. More specifically, when a port number included
15 in the header of a received frame matches a port number of the real-time application, it is judged that the application of the host layer is a real-time application. Further, the frame forwarding installation on the side of the transmitting terminal has an address
20 table which specifies a plurality of interface units in association with a destination address. If the application of the host layer is a real-time application, the frame forwarding installation sends a received frame to a plurality of paths via a plurality
25 interface units that conform to a destination address. Further, the frame forwarding installation on the side of the transmitting terminal attaches a tag, which includes a frame identifier, to a frame and then sends

the frame to a plurality of paths.

A frame forwarding installation on the side of a destination terminal stores the identifier of a frame, which has been received from a path and transmitted to the destination terminal, in a memory, checks to determine whether a frame identifier of a frame newly received from a path has been stored in the memory and, if the frame identifier has been stored in the memory, discards this received frame by reason of the fact that this frame has already been received. If the frame has not already been received, the frame forwarding installation transmits this received frame to the destination terminal and stores the identifier of this received frame. In this case, the frame identifier is a sequence number included in a header, or a computational result obtained by subjecting a specific portion of the received frame to a fixed computation, or a frame identifier included in a tag that has been attached to a received frame.

If the arrangement described above is adopted, a frame having a real-time property, such as voice or a moving image, can be sent to a plurality of paths simultaneously. If one path becomes congested or fails, the frame can be received from another normal path. This makes it possible to improve the quality and reliability of communication.

According to a second aspect of the present invention, a frame forwarding installation on the side

of a transmitting terminal sends a received frame in the direction of a destination over a plurality of paths if the type of a host application of the transmitting terminal is a predetermined type, e.g., if the host application is an application that places importance on quality/reliability. A frame forwarding installation on the side of a destination terminal sends a first arriving frame to the destination terminal and discards later arriving frames. If this arrangement is adopted, frames requiring high quality / high reliability can be sent to a plurality of paths simultaneously and communication quality and reliability can be improved even if a path becomes congested or develops a fault.

According to a third aspect of the present invention, a frame forwarding installation on the side of a transmitting terminal sends a received frame in the direction of a destination over a plurality of paths if a destination address or destination-source address of the received frame matches an address that has already been registered. A frame forwarding installation on the side of a destination terminal sends a first arriving frame to the destination terminal and discards later arriving frames. If this arrangement is adopted, a frame can be communicated with high quality and high reliability, even if a path develops congestion or a fault, by registering beforehand a transmission-source address for transmitting a frame requiring a real-time property or high quality / high reliability or a

Other features and advantages of the present invention will be apparent from the following

BRIEF DESCRIPTION OF THE DRAWINGS

10 Fig. 2 is a block diagram illustrating the
construction of a frame forwarding installation
according to a first embodiment of the present
invention;

15 Fig. 4 is a block diagram illustrating a
modification of the frame forwarding installation
according to the first embodiment;

Fig. 6 is a flowchart of second transmission processing executed by a frame forwarding installation on the side of a transmitting terminal;

Fig. 8 is a flowchart of second reception processing executed by a frame forwarding installation

on the side of a receiving terminal;

Fig. 9 is a block diagram illustrating the construction of a frame forwarding installation according to a second embodiment of the present invention;

Fig. 10 is a flowchart of third transmission processing executed by a frame forwarding installation on the side of a transmitting terminal;

Fig. 11 is a block diagram illustrating the construction of a frame forwarding installation according to a third embodiment of the present invention;

Fig. 12 is a diagram useful in describing a frame to which a tag has been attached;

Fig. 13 is a flowchart of fourth transmission processing executed by a frame forwarding installation on the side of a transmitting terminal;

Fig. 14 is a flowchart of fifth transmission processing executed by a frame forwarding installation on the side of a transmitting terminal;

Fig. 15 is a flowchart of third reception processing executed by a frame forwarding installation on the side of a receiving terminal;

Fig. 16 is a block diagram illustrating a modification of the frame forwarding installation according to the third embodiment;

Fig. 17 is a block diagram illustrating the construction of a frame forwarding installation

according to a fourth embodiment of the present invention; and

Fig. 18 is a flowchart of sixth transmission processing executed by a frame forwarding installation on the side of a transmitting terminal.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

(A) Overview of the present invention

Figs. 1A and 1B are diagrams useful in describing an overview of the present invention, in which Fig. 1A is for describing an improvement in quality and Fig. 1B an improvement in reliability. Shown in Figs. 1A and 1B are a transmitting terminal 10, a destination terminal 11, nodes (frame forwarding installations such as routers and switches) 12 to 17 constructing a backbone LAN, and paths 18₁ to 18₈ connecting the nodes. The node 12 is a frame forwarding installation on the side of the transmitting terminal and receives a frame sent from the transmitting terminal, and the node 15 is a frame forwarding installation on the side of the destination terminal and transmits a frame, which has been received from a path, to the destination terminal 11. Though not illustrated, each node constructs a separate branch LAN.

(a) Transmission of frames having a real-time property

The frame forwarding installation 12 determines whether a host application of the transmitting terminal 10 is a real-time application upon referring to the

header of a frame received from the transmitting terminal 10. If the application is a real-time application, the frame forwarding installation sends the received frame in the direction of the destination over the plurality of paths 18₁, 18₄. The frame forwarding installation 15 on the side of the destination terminal stores the identifier of the frame, which has been received from a path and transmitted to the destination terminal 11, in a memory. The frame forwarding installation 15 determines whether the frame identifier of a newly received frame has been stored in the memory, i.e., whether this frame has already been received. If the frame has already been received, the frame forwarding installation 15 discards this received frame. If the frame has not already been received, the frame forwarding installation 15 transmits this received frame to the destination terminal 11 and stores the identifier of this received frame. If one path PT₂ of two paths PT₁, PT₂ becomes congested (Fig. 1A), or if path PT₂ develops a fault (Fig. 1B), the frame from the path PT₁ will arrive at the frame forwarding installation 15 first and the frame forwarding installation 15 will transmit this frame to the destination terminal 11 and discard the frame that arrives later via the path PT₂ (Fig. 1A). It should be noted that if a path becomes faulty in Fig. 1B, there will be no later arriving frame.

If this arrangement is adopted, a frame having a

real-time property, such as voice or a moving image, can be sent to a plurality of paths simultaneously. Even if a path becomes congested or faulty, it is possible to improve the quality and reliability of communication of frames having a real-time property. Since a frame which does not have a real-time property is sent on a single path as heretofore, it is possible reduce the frequency of network congestion.

(b) Transmission of frames that place importance on quality/reliability

If it is found by referring to the header of a frame received from the transmitting terminal 10 that the type of host application of the transmitting terminal is a predetermined type, e.g., that the host application is one which emphasizes quality/reliability (one example of such an application is an FTP application), then the frame forwarding installation 12 sends the received frame in the direction of the destination over the plurality of paths 18₁, 18₄.

Operation from this point onward is similar to that in the case of a real-time application. If this arrangement is adopted, frames requiring high quality / high reliability can be sent to a plurality of paths simultaneously and communication quality and reliability can be improved even if a path becomes congested or develops a fault. Since a frame which does not require high quality / high reliability is sent on a single path as heretofore, it is possible reduce the frequency of

network congestion.

(c) If addresses match

If a destination address or transmission-source address included in the header of a frame received from the transmitting terminal 10 matches an address already registered, the frame forwarding installation 12 sends the received frame in the direction of the destination over the plurality of paths 18₁, 18₄. Operation from this point onward is similar to that in the case of a real-time application. If this arrangement is adopted, a frame can be communicated with high quality and high reliability, even if a path develops congestion or failure, by registering beforehand a transmission-source address for transmitting a frame requiring a real-time property or high quality / high reliability or a destination-terminal address which desires to receive a frame having a high quality / high reliability. This makes it possible to provide terminals and hosts with a high level of service in terms of quality and reliability.

(B) First embodiment

(a) Frame forwarding installation

Fig. 2 is a block diagram showing the construction of a frame forwarding installation according to a first embodiment of the present invention.

An input/output interface 21 sends frames to and receives frames from a terminal on the side of a branch LAN. Connected to the input/output interface 21 are a

receive buffer 22 for temporarily storing a frame received from a terminal, and a transmitting unit 23 for transmitting the frame to a terminal. The output side of the receive buffer 22 and the input side of the transmitting unit 23 are connected to a switch 24. The frame output from the receive buffer 22 is input to the switch 24 and is input also to a TCP port number monitor 25 and destination address recognition unit 26. The TCP port number monitor 25 refers to a TCP/UDP header and determines whether a host application of the transmitting terminal is a real-time application. If it is assumed that a real-time application has to be recognized from a frame which uses a protocol for a real-time application, e.g., the RTP (Real-time Transport Protocol), the TCP port number monitor 25 refers to a port number contained in the TCP/UDP header and determines whether the host application is a real-time application. The reason for this is that a port number 5004 has been assigned as the RTP default value.

If the host application is a real-time application, a multiple-path transmission discriminator 27 instructs a routing processor 28 to send a received frame to a plurality of paths (e.g., two paths). Further, the destination address recognition unit 26 extracts the destination address contained in an IP header and inputs this address to the routing processor 28. The latter has an address table 29 (see Fig. 3) for specifying a plurality of input/output interfaces associated with a

5

10

20

25

The redundant-frame filter 35, which has a received-frame table 36 for storing the identifier of a frame received from a backbone path and sent to the switch 24, determines whether the frame identifier of a frame output from the receive buffers 31, 32 has been stored in the received-frame table 36. If the frame identifier has been stored in the table 36, i.e., if the frame has already been received, the redundant-frame filter 35 discards this frame. If the frame is not one that has already been stored, however, the redundant-frame filter 35 outputs this frame to the switch side and stores the identifier of the frame in the received-frame table 36. As a result, even though the same frame is sent to a plurality of paths, only the first arriving frame is accepted and the later arriving frames are discarded. The frame identifier that has been stored in the received-frame table 36 is erased upon elapse of a fixed length of time.

A destination address recognition unit 37 extracts the destination address from a frame that has not been discarded by the redundant-frame filter 35 and inputs this address to a routing processor 38. The latter executes routing processing and notifies the switch 24 of the destination to which the frame is to be sent. For example, if the received frame is to be transmitted to a terminal, the routing processor 38 instructs the switch 24 to send the frame to the input/output interface 21. On the other hand, if the received frame

is to be sent to an output path that is different from the input path, the routing processor 38 instructs the switch 24 to send the frame to the input/output interface that conforms to this output path.

5 In order to simplify the description, the destination address recognition units 26, 37 are separately provided and so are the routing processors 28, 38. However, an arrangement can be adopted in which the apparatus shares a single destination address
10 recognition unit and a single routing processor. Fig. 4 illustrates an example of the arrangement of a frame forwarding installation in which the destination address recognition unit 26 and the routing processor 28 are shared.

15 (b) Modification

 In the description rendered above, the TCP port number monitor 25 refers to a TCP/UDP header to determine whether the host application of a transmitting terminal is a real-time application. However, the
20 following arrangement can also be adopted:
Specifically, in a modification, the TCP port number monitor 25 determines whether the type of a host application is a predetermined type, e.g., if the host application is an application that places importance on
25 quality/reliability. If the decision rendered is "YES", then the TCP port number monitor 25 instructs the multiple-path transmission discriminator 27 to send a received frame to a plurality of paths. An example of

an application that places importance on quality/reliability is one that uses an FTP protocol, wherein the port number of the FTP protocol is "21". Accordingly, the TCP port number monitor 25 determines
5 whether a host application is an application that places importance on quality/reliability by referring to the port number of the TCP/UDP header.

If the host application is an application that places importance on quality/reliability, the multiple-
10 path transmission discriminator 27 instructs the routing processor 28 to send the received frame to a plurality of paths (e.g., to two paths).

(c) Transmission processing

(c-1) When reference is made to a real-time
15 application

Fig. 5 is a flowchart of transmission processing executed by a frame forwarding installation on the side of a transmitting terminal for sending a frame to a plurality of paths in a case where a host application is
20 a real-time application.

If a frame is received from the terminal of a branch LAN, the TCP port number monitor 25 refers to the TCP port number of the TCP header (step 101) and determines whether the host application is a real-time
25 application (step 102). If the application is not a real-time application, the routing processor 28 instructs the switch 24 to send the received frame to one path that conforms to the destination address (step

103). If the application is a real-time application, however, then the multiple-path transmission discriminator 27 instructs the routing processor 28 to send the received frame to a plurality of paths. As a result, the routing processor 28 refers to the address table 29 and controls the switch 24 in such a manner that the received frame is sent to two or more paths conforming to the destination address (step 104). The above-described processing is thenceforth repeated whenever a frame is received from a terminal, thereby sending frames to the network paths of the backbone LAN.

(c-2) When reference is made to an application that emphasizes quality/reliability

Fig. 6 is a flowchart of transmission processing executed by a frame forwarding installation on the side of a transmitting terminal for sending a frame to a plurality of paths in a case where a host application is an application that places importance upon quality/reliability.

If a frame is received from the terminal of a branch LAN, the TCP port number monitor 25 refers to the TCP port number of the TCP header (step 111) and determines whether the host application is an application that places importance upon quality/reliability (step 112). If the application is not an application that places importance upon quality/reliability, the routing processor 28 instructs the switch 24 to send the received frame to one path

that conforms to the destination address (step 113). If the application is an application that places importance upon quality/reliability, however, then the multiple-path transmission discriminator 27 instructs the routing processor 28 to send the received frame to a plurality of paths. As a result, the routing processor 28 refers to the address table 29 and controls the switch 24 in such a manner that the received frame is sent to two or more paths conforming to the destination address (step 114). The above-described processing is thenceforth repeated whenever a frame is received from a terminal, thereby sending frames to the network paths of the backbone LAN.

(d) Reception processing

(d-1) When a sequence number is adopted as a frame identifier

Fig. 7 is a flowchart of reception processing executed by a frame forwarding installation on the side of a destination terminal.

The redundant-frame filter 35 of the frame forwarding installation on the side of the destination terminal checks to see whether a frame has been received from a path of a backbone LAN (step 151). If a frame has been received, the redundant-frame filter 35 extracts the frame identifier (e.g., the sequence number SN of the TCP header) from the received frame (step 152), checks to determine whether the frame identifier is present in the received-frame table 36 (step 153)

executed.

Thus, even though the same frame is sent to a plurality of paths from the frame forwarding installation on the side of the transmitting terminal, the frame forwarding installation on the side of the destination terminal accepts only the first arriving frame, transmits this frame to the destination terminal and discards later arriving frames.

Though the sequence number of a TCP header is adopted as the frame identifier in the description given above, the checksum (CS) of the TCP header can also be used as a frame identifier.

(d-2) When a computational result is adopted as a frame identifier

Fig. 8 is a flowchart of different reception processing executed by a frame forwarding installation on the side of a destination terminal.

The redundant-frame filter 35 of the frame forwarding installation on the side of the destination terminal checks to see whether a frame has been received from a path (step 201). If a frame has been received, the redundant-frame filter 35 subjects a specific portion of the frame to a fixed computation, obtains the result of the computation and adopts the result as the frame identifier (step 202). For example, the redundant-frame filter 35 applies a CRC operation or a checksum operation to the data portion of the frame from which the header is excluded (i.e., to the payload) and

frame and the present time (registration time) in the received-frame table 36 (step 208). Processing is then executed from step 205 onward.

It should be noted that if a frame is not received at step S201, processing from step 205 onward is executed.

Thus, even though the same frame is sent to a plurality of paths from the frame forwarding installation on the side of the transmitting terminal, the frame forwarding installation on the side of the destination terminal accepts only the first arriving frame, transmits this frame to the destination terminal and discards later arriving frames.

(C) Second embodiment

Fig. 9 is a block diagram showing the construction of a frame forwarding installation according to a second embodiment of the present invention. Components in Fig. 9 identical with those of the first embodiment shown in Fig. 2 are designated by like reference characters. This embodiment differs from the first embodiment in that the TCP port number monitor of the first embodiment is deleted and, instead, an address storage unit 41 for storing an address for which performance/reliability is important is provided. The transmission-source address of a terminal which transmits a frame requiring a real-time property or high quality / high reliability or a destination address of a terminal which desires a frame having a high quality / high reliability is registered

in the address storage unit 41 in advance. In this case, the registered address is a MAC address, IP address or address that is a combination of the MAC and IP addresses.

5 The multiple-path transmission discriminator 27 acquires the destination address or transmission-source address of a frame, which has been received from a terminal, from the destination address recognition unit 26, checks to determine whether this address matches an
10 address that has been stored in the address storage unit 41 and, if a matching address is found, instructs the routing processor 28 to send the received frame to a plurality of paths in the direction of the destination. When the routing processor 28 is so instructed to send
15 the frame to a plurality of paths, the routing processor 28 refers to the address table 29, obtains two input/output interfaces (e.g., input/output interfaces 30₁, 30₂) conforming to the destination address and instructs the switch 24 to send the frame to the
20 interfaces 30₁, 30₂.

Fig. 10 is a flowchart of transmission processing executed by a frame forwarding installation on the side of a transmitting terminal according to a second embodiment of the present invention.

25 If a frame is received from a terminal, the multiple-path transmission discriminator 27 refers to the destination address or transmission-source address in the header (step 301) and determines whether the

address has been registered in the address storage unit 41 (step 302). If the address has not been registered, the routing processor 28 sends the received frame to a single path conforming to the destination address via the switch 24 (step 303). If the address has been stored in the address storage unit 41, however, the multiple-path transmission discriminator 27 instructs the routing processor 28 to send the received frame to a plurality of paths. As a result, the routing processor 28 refers to the address table 29 and controls the switch 24 so as to send the received frame to two or more paths conforming to the destination address (step 304). The above-described processing is thenceforth repeated whenever a frame is received from a terminal, thereby sending frames to the network paths of the backbone LAN.

The reception processing executed by the frame forwarding installation of the second embodiment adopts the reception processing of Figs. 7 and 8. In accordance with the second embodiment, terminals and hosts can be provided with a high level of service in terms of quality and reliability.

(D) Third embodiment

Fig. 11 is a block diagram showing the construction of a frame forwarding installation according to a third embodiment of the present invention. Components in Fig. 11 identical with those of the first embodiment shown in Fig. 2 are designated by like reference characters.

This embodiment differs in the following respects:

(1) Tag attaching units 51, 52 are provided between the transmitting units 33, 34 and the switch 24. In accordance with a command from the routing processor 5 28, the tag attaching units 51, 52 each attach a tag to a frame, which is directed to the destination terminal, received from the path of a branch LAN and send the frame to a path of a backbone LAN.

(2) A tag removal unit 53 is provided between the 10 redundant-frame filter 35 and the switch 24. The tag removal unit 53 removes a tag from a frame, which is directed to the destination terminal, received from the path of a backbone LAN and inputs the frame without the tag to the switch 24.

15 The tag is attached to the frame in order to specify the frame identifier and is applicable to a case where data for identifying a frame, such as a sequence number SN, is not contained in the header. Fig. 12 is a diagram useful in describing a frame to which a tag TG 20 has been attached. The tag TG includes at least a frame identifier FRID and, when appropriate, a destination address, a transmission-source address and a control signal.

(a) Transmission processing

25 (a-1) When reference is made to a real-time application

Fig. 13 is a flowchart of transmission processing executed by a frame forwarding installation on the side

of a transmitting terminal for sending a frame to a plurality of paths in a case where a host application is a real-time application.

If a frame is received, the frame forwarding
5 installation refers to the TCP port number in the frame (step 401) and determines whether the host application is a real-time application (step S402). If the application is not a real-time application, the frame forwarding installation sends the received frame to one
10 path that conforms to the destination address (step 403). If the application is a real-time application, however, then the multiple-path transmission discriminator 27 instructs the routing processor 28 to send the received frame to a plurality of paths.

15 As a result, the routing processor 28 refers to the address table 29, controls the switch 24 so as to send the received frame to two or more paths that conform to the destination address and instructs the tag attaching units 51, 52 to create and attach a tag. In response,
20 the tag attaching units 51, 52 each create a tag, which includes the frame identifier, and attach the tag to the frame (step 404). Next, the frame with the attached tag is sent to two or more paths conforming to the destination address via the transmitting units 33, 34
25 and input/output interfaces 30₁, 30₂ (step 405). The above-described processing is thenceforth repeated whenever a frame is received from a terminal, thereby sending frames to the paths of the backbone LAN.

(a-2) When reference is made to an application
that emphasizes quality/reliability

Fig. 14 is a flowchart of transmission processing
executed by a frame forwarding installation on the side
5 of a transmitting terminal for sending a frame to a
plurality of paths in a case where a host application is
an application that places importance upon
quality/reliability.

If a frame is received from a transmitting
10 terminal, the frame forwarding installation refers to
the TCP port number in the frame (step 451) and
determines whether the host application is an
application that places importance upon
quality/reliability (step S452). If the application is
15 not an application that places importance upon
quality/reliability, the frame forwarding installation
sends the received frame to one path that conforms to
the destination address (step 453). If the application
is an application that places importance upon
20 quality/reliability, however, then the multiple-path
transmission discriminator 27 instructs the routing
processor 28 to send the received frame to a plurality
of paths.

As a result, the routing processor 28 refers to the
25 address table 29, controls the switch 24 so as to send
the received frame to two or more paths that conform to
the destination address and instructs the tag attaching
units 51, 52 to create and attach a tag. In response,

the tag attaching units 51, 52 each create a tag, which includes the frame identifier, and attach the tag to the frame (step 454). Next, the frame with the attached tag is sent to two or more paths conforming to the destination address via the transmitting units 33, 34 and input/output interfaces 30₁, 30₂ (step 455). The above-described processing is thenceforth repeated whenever a frame is received from a terminal, thereby sending frames to the network paths on the network side.

10 (b) Reception processing

Fig. 15 is a flowchart of reception processing executed by a frame forwarding installation on the side of a destination terminal.

The redundant-frame filter 35 of the frame forwarding installation on the side of the destination terminal checks to see whether a frame has been received from a path of the backbone LAN (step 501). If a frame has been received, the redundant-frame filter 35 extracts the frame identifier contained in the tag (step 502), checks to determine whether the frame identifier is present in the received-frame table 36 (step 503) and, if it is, discards the received frame (step 504). Next, it is determined whether frame identifiers that have been registered in the received-frame table 36 include a frame identifier that has been registered for a period of time greater than a fixed period of time (step 505). If the decision rendered is "YES", then this frame identifier is deleted from the table (step

506). If the decision rendered is "NO", then no particular operation is performed and control returns to the beginning to repeat the above-described processing.

If it is determined at step S503 that the frame identifier does not exist in the received-frame table 36, on the other hand, the redundant-frame filter 35 outputs the received frame to the switch side and the tag removal unit 53 removes the tag from the frame (step 507). The routing processor 38 then refers to the destination address, recognizes that the frame is one to be sent to a terminal and controls the switch so as to transmit the received frame to the destination terminal (step 508). Thereafter, the redundant-frame filter 35 enters the frame identifier of the tag of the received frame and the present time (registration time) in the received-frame table 36 (step 509). Processing is then executed from step 505 onward. If a frame is not received at step S151, processing from step 505 onward is executed.

Thus, even though the same frame is sent to a plurality of paths from the frame forwarding installation on the side of the transmitting terminal, the frame forwarding installation on the side of the destination terminal accepts only the first arriving frame, transmits this frame to the destination terminal and discards later arriving frames.

In Fig. 11, the destination address recognition units 26, 37 are separately provided and so are the

routing processors 28, 38. However, an arrangement can be adopted in which the apparatus shares a single destination address recognition unit and a single routing processor. Fig. 16 illustrates an example of the arrangement of a frame forwarding installation in which the destination address recognition unit 26 and the routing processor 28 are shared.

(E) Fourth embodiment

Fig. 17 is a block diagram showing the construction of a frame forwarding installation according to a fourth embodiment of the present invention. Components in Fig. 17 identical with those of the second embodiment shown in Fig. 9 are designated by like reference characters. This embodiment differs in the following respects:

(1) Tag attaching units 51, 52 are provided between the transmitting units 33, 34 and the switch 24 and, in accordance with a command from the routing processor 28, the tag attaching units 51, 52 each attach a tag to a frame, which has been received from a terminal, and send the frame to a path of the backbone LAN.

(2) The tag removal unit 53 is provided between the redundant-frame filter 35 and the switch 24. The tag removal unit 53 removes a tag from a frame, which is directed to the destination terminal, received from the path of a backbone LAN and inputs the frame without the tag to the switch 24.

Fig. 18 is a flowchart of transmission processing

executed by a frame forwarding installation according to the fourth embodiment.

If a frame is received from the transmitting terminal, the multiple-path transmission discriminator 5 27 of the frame forwarding installation refers to the destination address or transmission-source address in the header via the destination address recognition unit 26 (step 601) and checks to see whether this address has been registered in the address storage unit 41 (step 10 602). If the address has not been registered, the routing processor 28 sends the received frame to one path that conforms to the destination address via the switch 24 (step 603). If the address has been registered in the address storage unit 41, however, the 15 multiple-path transmission discriminator 27 instructs the routing processor 28 to send the received frame to a plurality of paths.

As a result, the routing processor 28 refers to the address table 29, controls the switch 24 so as to send 20 the received frame to two or more paths that conform to the destination address and instructs the tag attaching units 51, 52 to create and attach a tag. In response, the tag attaching units 51, 52 each create a tag, which includes the frame identifier, and attach the tag to the 25 frame (step 604). Next, the frame with the attached tag is sent to two or more paths conforming to the destination address via the transmitting units 33, 34 and input/output interfaces 30₁, 30₂ (step 605). The

above-described processing is thenceforth repeated whenever a frame is received from a terminal, thereby sending frames to the paths of the backbone LAN

Reception processing according to the fourth
5 embodiment is the same as that shown in Fig. 15.

Thus, in accordance with the present invention, a frame having a real-time property, such as voice or a moving image, can be sent to a plurality of paths simultaneously. Even if one path becomes congested or
10 fails, the frame can be received from another normal path. This makes it possible to improve the quality and reliability of communication.

Further, in accordance with the present invention, frames requiring high quality / high reliability can be
15 sent to a plurality of paths simultaneously and communication quality and reliability can be improved even if a path becomes congested or develops a fault.

Further, in accordance with the present invention, a frame can be communicated with high quality and high
20 reliability, even if a path develops congestion or fault, by registering beforehand a transmission-source address for transmitting a frame requiring a real-time property or high quality / high reliability or a destination-terminal address which desires to receive a
25 frame having a high quality / high reliability.

As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be understood

that the invention is not limited to the specific
embodiments thereof except as defined in the appended
claims.

WHAT IS CLAIMED IS:

1. A frame forwarding installation for sending a received frame to a path conforming to a destination address contained in a header of the frame, which has
5 been received from a transmitting terminal, comprising:
an application discriminating unit for referring to a header of a received frame and determining whether an application of a host layer in the transmitting terminal is a real-time application; and
10 a frame transmitting unit for sending the received frame to a plurality of paths in the direction of a destination if the application is a real-time application.
2. The frame forwarding installation according to claim
15 1, wherein said application discriminating unit determines that the application of the host layer is a real-time application when a port number of the received frame matches a port number of the real-time application.
- 20 3. The frame forwarding installation according to claim 1, further comprising a plurality of interface units;
wherein said frame transmitting unit has an address table which specifies a plurality of interface units in association with a destination address and sends the
25 received frame to a plurality of paths via a plurality of interface units, which conform to a destination address, if the application is a real-time application.
4. The frame forwarding installation according to claim

of interface units, which conform to a destination address, if the type application is the predetermined type.

8. The frame forwarding installation according to claim 5, further comprising a tag attaching unit for attaching a tag, which includes a frame identifier, to a frame;

wherein a frame forwarding installation on the side of a receiving terminal utilizes the frame identifier when determining whether an identical frame has already been received or not.

9. A frame forwarding installation for sending a received frame to a path conforming to a destination address contained in a header of the frame, which has been received from a transmitting terminal, comprising:

an address-match discriminating unit for determining whether a destination address or transmission-source address contained in a header of a received frame matches an address that has already been registered; and

a frame transmitting unit for sending the received frame to a plurality of paths in the direction of a destination if the addresses match.

10. The frame forwarding installation according to claim 9, further comprising a plurality of interface units;

wherein said frame transmitting unit has an address table which specifies a plurality of interface units in association with a destination address and sends the

number contained in the frame.

14. The frame forwarding installation according to claim 12, wherein the frame identifier is a computational result obtained by subjecting a specific portion of the received frame to a fixed computation.

15. The frame forwarding installation according to claim 12, wherein the frame identifier is a frame identifier contained in a tag that has been attached to a received frame.

10 16. A network having a frame forwarding installation for sending a received frame to a path conforming to a destination address contained in a header of the frame, which has been received from a transmitting terminal, and a frame forwarding installation for receiving a
15 frame, which is directed toward a subordinate destination terminal, from a path and transmitting the frame to the destination terminal, wherein the frame forwarding installation on the side of the transmitting terminal comprises:

20 an application discriminating unit for referring to a header of a received frame and determining whether an application of a host layer in the transmitting terminal is a real-time application; and

a frame transmitting unit for sending the received
25 frame to a plurality of paths in the direction of a destination if the application is a real-time application; and

the frame forwarding installation on the side of

003040" is 4.4360

a storage unit for storing an identifier of a frame that has been transmitted to the destination terminal;
and

5 a redundant-frame filter for determining whether a
frame identifier of a newly received frame has been
stored in said storage unit, discarding the received
frame if the frame is a frame that has already been
received, and transmitting the received frame to the
10 destination terminal and storing the identifier of the
received frame in said storage unit if the frame is not
a frame that has already been received.

17. A network having a frame forwarding installation for sending a received frame to a path conforming to a destination address contained in a header of the frame, which has been received from a transmitting terminal, and a frame forwarding installation for receiving a frame, which is directed toward a subordinate destination terminal, from a path and transmitting the frame to the destination terminal, wherein the frame forwarding installation on the side of the transmitting terminal comprises:

an application-type discriminating unit for referring to a header of a received frame and discriminating the type of application of a host layer in the transmitting terminal; and

a frame transmitting unit for transmitting the received frame to a plurality of paths in the direction

the frame forwarding installation on the side of the destination terminal comprises:

a redundant-frame filter for determining whether a frame identifier of a frame newly received from a path has been stored in said storage unit, discarding the received frame if the frame is a frame that has already been received, and transmitting the received frame to the destination terminal and storing the identifier of the received frame in said storage unit if the frame is not a frame that has already been received.

an address-match discriminating unit for determining whether a destination address or transmission-source address contained in a header of a

received frame matches an address that has already been registered; and

a frame transmitting unit for sending a received frame to a plurality of paths in the direction of a destination if the addresses match; and

the frame forwarding installation on the side of the destination terminal comprises:

a storage unit for storing an identifier of a frame that has been transmitted to the destination terminal; and

a redundant-frame filter for determining whether a frame identifier of a frame newly received from a path has been stored in said storage unit, discarding the received frame if the frame is a frame that has already been received, and transmitting the received frame to the destination terminal and storing the identifier of the received frame in said storage unit if the frame is not a frame that has already been received.

03010" 43E4360

A frame forwarding installation on the side of a transmitting terminal refers to a header of a received frame and determines whether a host application is a real-time application. If the application is a real-time application, the received frame is sent to a plurality of paths in the direction of a destination. When a frame received from a path is transmitted to a destination terminal, a frame forwarding installation on the side of the destination terminal stores the identifier of this frame in a storage unit and, if a frame then newly arrives from a path, determines whether the frame identifier of this frame has been stored in the storage unit. If the newly arriving frame has been stored, it is regarded as being a frame already received and is discarded. If the newly arriving frame is not a frame that has already been received, the received frame is transmitted to the destination terminal and the identifier of this frame is stored.

20

FIG. 1A




FIG. 1B




FIG. 2




FIG. 3

DESTINATION ADDRESS	INPUT/OUTPUT INTERFACE	SUCCEEDING FRAME FORWARDING INSTALLATION (ROUTER)
A1		
A2		
---	---	---

FIG. 12




FIG. 4






FIG. 5

FIG. 6

7/17
FIG. 7




FIG. 8




FIG. 9





FIG. 10

FIG. 11





FIG. 13




FIG. 15




FIG. 16






FIG. 17





Declaration and Power of Attorney For Patent Application**特許出願宣言書及び委任状****Japanese Language Declaration****日本語宣言書**

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

FRAME FORWARDING INSTALLATION

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

TOKUGANHEI 11-171941 Japan
(Number) (Country)
(番号) (国名)

(Number) (Country)
(番号) (国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.) (Filing Date)
(出願番号) (出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.) (Filing Date)
(出願番号) (出願日)

(Application No.) (Filing Date)
(出願番号) (出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

18/06/1999
(Day/Month/Year Filed)
(出願年月日)

(Day/Month/Year Filed)
(出願年月日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.) (Filing Date)
(出願番号) (出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration
(日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の
手続きを米特許商標局に対して遂行する弁理士または代理人
として、下記の者を指名いたします。(弁理士、または代理
人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint
the following attorney(s) and/or agent(s) to prosecute this
application and transact all business in the Patent and Trademark
Office connected therewith (list name and registration number)

書類送付先

Aaron B. KARAS, Reg. No. 18,923; Samson HELFGOTT,
Reg. No. 23,072 and Leonard COOPER Reg. No. 27,625
Send Correspondence to:
HELFGOTT & KARAS, P.C.
Empire State Building, 60th Floor
New York, New York 10118
United States of America

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Helfgott & Karas, P.C.
(212) 643-5000

唯一または第一発明者名	Full name of sole or first inventor
Osamu Sekihata	
発明者の署名	Inventor's signature
日付	Date
住所	Residence
国籍	Citizenship
私書箱	Post Office Address
第二共同発明者	Full name of second joint inventor, if any
第二共同発明者	Second inventor's signature
住所	Residence
国籍	Citizenship
私書箱	Post Office Address

(第三以降の共同発明者についても同様に記載し、署名をす
ること)

(Supply similar information and signature for third and subsequent
joint inventors.)

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of: **Osamu SEKIHATA**

Filed: : **Concurrently herewith**

For : **FRAME FORWARDING INSTALLATION**

Serial No.: **Concurrently herewith**

April 5, 2000


Assistant Commissioner of Patents
Washington, D.C. 20231

SUB-POWER OF ATTORNEY

S I R:

I, Aaron B. Karas, Reg. No. 18,923 attorney of record herein, do hereby grant a sub-power of attorney to Linda S. Chan, Reg. No. 42,400, Jacqueline M. Steady, Reg. No., 44,354 and Harris A. Wolin, Reg. No. 39,432 to act and sign in my behalf in the above-referenced application.

Respectfully submitted,


Aaron B. Karas
Reg.No 18,923

HELFGOTT & KARAS, P.C.
60th FLOOR
EMPIRE STATE BUILDING
NEW YORK, NY 10118
DOCKET NO.: FUSA17.211
LHH:power

Filed Via Express Mail
Rec. No.: EL522391655US
On: April 5, 2000
By: Lydia Gonzalez
Any fee due as a result of this paper,
not covered by an enclosed check may be
charged on Deposit Acct. No. 08-1634.

003040-4544360